

LED4S WIRELESS







INTRODUCTION

The LED 4S Wireless is surface mount standalone non maintained emergency luminaire with both open area and escape route options and available in both black and white variants. The LED3s is available in two versions, either Reacta-Link wireless compatible or Reacta-Control wireless compatible, allowing emergency testing to be automated and test results to be centrally reported wirelessly substantially reducing the labour costs associated with emergency testing and offering a rapid return on investment.

CE IP20

APPLICATION

- Commercial / Offices
- Corridor
- Education
- Food / Clean Area
- Healthcare / Social Housing
- Hotel / Leisure
- Industrial / Manufacturing
- Retail

- Stairwell
- Transport
- Warehouse / Storage

SPECIFICATION

CONSTRUCTION

• Housing: 0.7mm CR4 steel

• Housing: Injection moulded polycarbonate

Finish: Matt blackFinish: Matt white

• Lens: Injection moulded PMMA lens

IP20

ENVIRONMENTAL

- Every luminaire is labelled with a unique ID number allowing easy identification of spare parts for the lifetime of the product.
- Contains no single use plastics or polystyrene packaging.
- UK based manufacturing providing local support throughout the product lifetime and minimising transportation miles.

EMERGENCY

- Optional Reacta-Link wireless emergency for automated centralised reporting.
- Optional Reacta-Control wireless emergency for automated centralised reporting.

INSTALLATION

- Suitable for conduit installation
- Suitable for surface installation

VARIATIONS

- Available in white or black finishes
- Supplied with three lens variants, open area, escape route and spot

IMAGES

PRODUCT IMAGES



LED4S Wireless





LED4S NM3 LA3RC CON



LED4S NM3 LA3RC CON Black

TECHNICAL





WARRANTY

At Dextra our commitment to service has been at the forefront throughout our history spanning more than forty years in the UK lighting market. Our service ethos extends beyond design and delivery, we believe supporting your installation throughout the warranty period is equally crucial, whilst the strength and longevity of Dextra Group provides peace of mind that our warranty will be supported throughout.

The Dextra range is supplied with a five year warranty commencing from the date of delivery. During the first three years defects will be repaired on site and the warranty will include both parts and labour. For the final two years drivers, emergency modules, wireless modules, sensors and LED circuits will be supplied free of charge to replace defective components, labour and other associated costs are not included.

Certain ranges and components are subject to exemptions:

- Lithium batteries are provided with a three year warranty for parts and labour. Nickel Metal Hydride and Nickel Cadmium batteries are provided with a one year warranty for parts and labour.
- Emergency luminaires including AME LED, EXI LED, EXI LED, EXI Track, HBE LED, HBE2 LED, OAT2 LED, OEZ LED and Twinspot with Nickel Metal Hydride batteries are supplied with a one year warranty for parts and labour. Lithium variants of these ranges are supplied with a three year warranty for parts and labour with the exception of the AME2, EXI3, HBE3 and TWS IP65 L7 ranges which are supplied with a one year parts and labour warranty. TWS IP65 L7 in autotest and wireless variants are supplied with the standard three year lithium battery warranty.
- Protec Micro, PTECF7 Fire Rated Downlights, Serenus and the Opus Sconce are provided with a five year replacement luminaire only warranty. Protec FR Fire Rated Downlights are provided with a 2 year replacement luminaire only warranty.
- Controls systems such as standalone sensors, switches, marshalling boxes and cabling are provided with a one year warranty for both parts and labour. DALI control systems are provided with a two year warranty for both parts and labour.
- LEDextra ranges are supplied with a three year parts or replacement luminaire only warranty with the exception of the IMPR RGBW, the Runway RBGW and the MOD RGBW. These three ranges are supplied with our standard five year warranty during which defects within the first three years will be repaired on site and the warranty includes both parts and labour. For the final two years free of charge replacement components only will be supplied to rectify any failures but labour and other associated costs are not included.
- LEDEX ranges are supplied with a three year replacement luminaire only warranty.

All warranties are subject to correct use of the product and will be invalidated by misuse, for example incorrect installation, unsuitable environmental conditions or incorrect maintenance. It is the duty of the customer to ensure that all the fault lies with the luminaire prior to requesting replacement parts or site repairs. In the event that no defect is found with the product our costs for attending site will be recharged to the customer and credit will not be issued against returned products. No consequential losses incurred resulting from any defect with our product will be reimbursed.

Given the nature of LED technology a small percentage of LEDs may fail during the lifetime of a luminaire, this does not cause a reduction in lumen output. As such LED luminaires are only deemed to be faulty for warranty purposes when in excess of ten percent of LEDs have failed in a single luminaire

On site repair of products under warranty will be undertaken during normal working hours, 9am to 5pm Monday to Friday, and will require unrestricted access to luminaires. Where required Dextra will provide access equipment to carry out repairs at height, should luminaires have been installed in locations where reasonable provision for maintenance access has not been made we reserve the right to supply replacement product only.

If you require any assistance with regards to our products please contact our Customer Services department on 01747

858100.

DOWNLOAD WARRANTY PDF

ORDER CODES

LUMINAIRE

Code	Description	Power
LED4S NM3 LA3RC CON	LED4S Surface, Reacta-Control, White, 338llm	4.0W
LED4S NM3 LA3RC CON BL	LED4S Surface, Reacta-Control, Black, 338llm	4.0W
LED40 STR	LED4 Open Area, Maintained (Non-Maintained Compatible), Reacta Link Wireless Emergency	
LED4E STR	LED4 Escape Route, Maintained (Non-Maintained Compatible), Reacta Link Wireless Emergency	
Lumen outputs for LA3R	C variants based on Open Area lens	

MISCELLANEOUS

Code	Description
LSF	Low Smoke Zero Halogen