



# PRODUCT SPECIFICATION

---

TYPHON



## INTRODUCTION

The Typhon is a robust and durable IP65 luminaire suitable for a wide range of industrial and commercial applications where protection against water and dust ingress and light impact is critical.

Manufactured with a glass reinforced polyester housing and supplied with stainless steel clips as standard, the Typhon offers excellent chemical resistance, whilst the polycarbonate diffuser ensures resilience against accidental impacts. The Typhon is supplied complete with snap on mounting clips for the luminaire rear providing both suspension and surface mounting points without the need to drill the luminaire housing, whilst the gear tray is mounted via spring release clips ensuring installation and ongoing maintenance can be undertaken quickly and simply.

The Typhon is available in both 1200mm and 1500mm variants in two housing widths and is suitable for use in temperatures ranging from -20°C to +25°C. All common dimming and lithium emergency variants are available as well as a wide range of lumen outputs. We offer a range of wireless control systems providing localised grouping and control as well as comprehensive wireless solutions allowing both standard and emergency luminaires to be centrally monitored.

UK CA	CE	IP65	IP66	IK08	TM21: L90>60K Hours / L80>90K Hours	3 STEP MACADAM ELLIPSE
----------	----	------	------	------	--	---------------------------

## APPLICATION

- Corridor
- Exterior
- Food / Clean Area

- Healthcare / Social Housing
- Hotel / Leisure
- Industrial / Manufacturing
- Parking / Exterior
- Retail
- Stairwell
- Store Room
- Transport
- Warehouse / Storage

---

## SPECIFICATION

---

### CONSTRUCTION

- Housing: Injection moulded glass reinforced polyester
- Finish: Matt grey
- Diffuser: Injection moulded high transmission opal polycarbonate
- IK08
- IP65

### PERFORMANCE

- Part L2 compliant
- 3SCDM Three step Macadams ellipse
- TM21: L90>60K Hours / L80>90K Hours
- Up to 155 luminaire lumens per circuit Watt.

### ENVIRONMENTAL

- Designed to allow simple replacement of components with commonly available tools in compliance with the Eco Design Directive, please see the installation leaflet for maintenance instructions.
- All critical components are mounted on a single tray for simple end of life repair or upgrade.
- Powered by European branded drivers and emergency modules ensuring replacement parts are easily sourced.
- Every luminaire is labelled with a unique ID number allowing easy identification of spare parts for the lifetime of the product.
- Contains no single use plastics or polystyrene packaging.
- Supplied in plain card boxes with paper tape ensuring packaging is easily recycled.
- Designed to allow simple disassembly for end of life recycling.
- UK based manufacturing providing local support throughout the product lifetime and minimising transportation miles.

### EMERGENCY

- Available with optional standard, self test and autotest integral emergency with lithium batteries for extended warranty and lifetime.
- Optional Reacta-Link wireless emergency for automated centralised reporting.

- Optional Reacta-Control wireless emergency for automated centralised reporting.
- Optional central battery changeover relay

#### CONTROL

- Optional compatibility with a range of dimming systems including DALI, DSI and Switch Dimming
- Optional White tunable
- Optional integral Reacta-Link for integration with Reacta-Link wireless installations
- Optional integral Reacta-Control for integration with Reacta-Control wireless installations

#### INSTALLATION

- Suitable for suspended installation
- Suitable for trunking installation
- Suitable for conduit installation
- Suitable for surface installation
- Suitable for external use when protected under canopy.

#### VARIATIONS

- Available with a wide range of colour temperatures and renderings
- Available in a range of housing sizes and lumen outputs

---

## IMAGES

---

#### PRODUCT IMAGES



Typhon Single 1200mm



Typhon Twin 1500mm



Typhon Single 1500mm



Typhon Single 1500mm Rear



Typhon Bracket





Typhon Suspension



#### PROJECT IMAGES





### TECHNICAL





## WARRANTY

At Dextra our commitment to service has been at the forefront throughout our history spanning more than forty years in the UK lighting market. Our service ethos extends beyond design and delivery, we believe supporting your installation throughout the warranty period is equally crucial, whilst the strength and longevity of Dextra Group provides peace of mind that our warranty will be supported throughout.

The Dextra range is supplied with a five year warranty commencing from the date of delivery. During the first three years defects will be repaired on site and the warranty will include both parts and labour. For the final two years drivers, emergency modules, wireless modules, sensors and LED circuits will be supplied free of charge to replace defective components, labour and other associated costs are not included.

Certain ranges and components are subject to exemptions:

- Lithium batteries are provided with a three year warranty for parts and labour. Nickel Metal Hydride and Nickel Cadmium batteries are provided with a one year warranty for parts and labour.
- Emergency luminaires including AME LED, EXI LED, EXI2 LED, EXI Track, HBE LED, HBE2 LED, OAT2 LED, OEZ LED and Twinspot with Nickel Metal Hydride batteries are supplied with a one year warranty for parts and labour. Lithium variants of these ranges are supplied with a three year warranty for parts and labour with the exception of the AME2, EXI3, HBE3 and TWS IP65 L7 ranges which are supplied with a one year parts and labour warranty. TWS IP65 L7 in autotest and wireless variants are supplied with the standard three year lithium battery warranty.
- Protec Micro, PTECF7 Fire Rated Downlights, Serenus and the Opus Sconce are provided with a five year replacement luminaire only warranty. Protec FR Fire Rated Downlights are provided with a 2 year replacement luminaire only warranty.
- Controls systems such as standalone sensors, switches, marshalling boxes and cabling are provided with a one year warranty for both parts and labour. DALI control systems are provided with a two year warranty for both parts and labour.

- LEDextra ranges are supplied with a three year parts or replacement luminaire only warranty with the exception of the IMPR RGBW, the Runway RGBW and the MOD RGBW. These three ranges are supplied with our standard five year warranty during which defects within the first three years will be repaired on site and the warranty includes both parts and labour. For the final two years free of charge replacement components only will be supplied to rectify any failures but labour and other associated costs are not included.
- LEDEX ranges are supplied with a three year replacement luminaire only warranty.

All warranties are subject to correct use of the product and will be invalidated by misuse, for example incorrect installation, unsuitable environmental conditions or incorrect maintenance. It is the duty of the customer to ensure that all the fault lies with the luminaire prior to requesting replacement parts or site repairs. In the event that no defect is found with the product our costs for attending site will be recharged to the customer and credit will not be issued against returned products. No consequential losses incurred resulting from any defect with our product will be reimbursed.

Given the nature of LED technology a small percentage of LEDs may fail during the lifetime of a luminaire, this does not cause a reduction in lumen output. As such LED luminaires are only deemed to be faulty for warranty purposes when in excess of ten percent of LEDs have failed in a single luminaire

On site repair of products under warranty will be undertaken during normal working hours, 9am to 5pm Monday to Friday, and will require unrestricted access to luminaires. Where required Dextra will provide access equipment to carry out repairs at height, should luminaires have been installed in locations where reasonable provision for maintenance access has not been made we reserve the right to supply replacement product only.

If you require any assistance with regards to our products please contact our Customer Services department on 01747 858100.

[DOWNLOAD WARRANTY PDF](#)

## ORDER CODES

### LUMINAIRE

Code	Description	Power	Llm/W
TYP L26 PC 4S	Typhon, 1200mm, 2,236llm, Polycarbonate Diffuser, Single, Colour 84	16.0W	140
TYP L38 PC 4S	Typhon, 1200mm, 3,268llm, Polycarbonate Diffuser, Single, Colour 84	23.8W	137
TYP L50 PC 4S	Typhon, 1200mm, 4,300llm, Polycarbonate Diffuser, Single, Colour 84	28.9W	149
TYP L87 PC 4T	Typhon, 1200mm, 7,343llm, Polycarbonate Diffuser, Twin, Colour 84	52.7W	139
TYP L35 PC 5S	Typhon, 1500mm, 3,010llm, Polycarbonate Diffuser, Single, Colour 84	22.2W	136
TYP L45 PC 5S	Typhon, 1500mm, 3,870llm, Polycarbonate Diffuser, Single, Colour 84	26.4W	146
TYP L54 PC 5S	Typhon, 1500mm, 4,644llm, Polycarbonate Diffuser, Single, Colour 84	33.4W	139
TYP L63 PC 5S	Typhon, 1500mm, 5,418llm, Polycarbonate Diffuser, Single, Colour 84	39.6W	137
TYP L80 PC 5S	Typhon, 1500mm, 6,880llm, Polycarbonate Diffuser, Single, Colour 84	47.7W	144
TYP L96 PC 5S	Typhon, 1500mm, 8,256llm, Polycarbonate Diffuser, Single, Colour 84	53.0W	156
TYP L120 PC 5S	Typhon, 1500mm, 10,320llm, Polycarbonate Diffuser, Single, Colour 84	70.1W	147
TYP L132 PC 5T	Typhon, 1500mm, 11,147llm, Polycarbonate Diffuser, Twin, Colour 84	78.5W	142
TYP L160 PC 5T	Typhon, 1500mm, 13,842llm, Polycarbonate Diffuser, Twin, Colour 84	84.4W	164
TYP L200 PC 5T	Typhon, 1500mm, 16,880llm, Polycarbonate Diffuser, Twin, Colour 84	107.9W	156



## DIMMING

Code	Description
A	DALI Digital Addressable Lighting Interface
S	Switch Dimming
D	DSI Digital Dimming
H	HFR Analogue 1-10v
C	Bi-Level Dimming For Standalone Switched Sensor
WT	White Tunable (Lumen Outputs Vary from Standard)
Please click <a href="#">here</a> for full details on our white tunable offer.	

## CONTROL

Code	Description
RC	Reacta-Control, Wireless Enabled Luminaire

## EMERGENCY

Code	Description
LE3	Lithium Standard Emergency 3 Hour
LS3	Lithium Selftest Emergency 3 Hour
LA3	Lithium Autotest Emergency 3 Hour
LSTR	Lithium Reacta-Link Emergency 3 Hour
LA3RC	Lithium Reacta-Control Emergency 3 Hour
CB	Central Battery, Please Specify 50V, 110V or 230V when Ordering
L120 and L200 variant are not available with emergency.	

## MISCELLANEOUS

Code	Description
C**	Select Colour Temperature and Rendering; C83, C84, C85, C865, C93, C94
LSF	Low Smoke Zero Halogen